Product data sheet


NEMESIS_7_BL_34W_NEUTRAL_MEDIUM_L2240MM_CRI90
99826302_
PETRIDIS



IP 20

NEMESIS is an ideal solution for small showcases, homes, rest areas, museums, hotels, exhibition halls and generally for many decorative and architectural projects. Available in Medium and Wide light distribution can be the perfect tool for wide range of applications. Technical Features - Aluminium body, painted electrostatically in selected colour. - Lens in Medium and Wide version. - Pure light without IR/UV radiation. - Low glare (UGR< 19). - Efficient thermal management. - Operation life: 50,000 hours with efficiency > 80% of the initial luminous flux (L80B10). - Connection for operation with constant current. Upon Request - Available with hightest colour rendering index (CRI).

Light output 1



1 x LED

Nominal lamp power	34 W	LOR	76%
Lamp flux	5020 lm	Total flux	3795 lm
Luminous efficacy	148 lm/W	Total power	34 W
CCT	4000 K		
CRI	90		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 88.19 in
Width: 1.73 in
Height: 3.23 in

Adjustability

Fixed

Design

Material impression: Aluminum, Plastic

Electric

System power: 34 W
Controller: Dimmable 1..10V, DALI
Suitable for feed-through wiring
Appliance Class: I

Protection

IP: 20
Designation labels: CE