


Product data sheet

WALL MOUNTED LUMINAIRE OSLO 650-2 - WITH LOUVERS 3000K
10.12430.0VXXX + 10.42400.0V001
HESS




Round luminaire canopy, horizontally split in two, made of aluminium, plain coloured. Support elements made of aluminium, painted.
Cylindrical luminaire enclosure made of PMMA. Round luminaire body made of aluminium, optionally with or without louvres. 10.42400.0V001
PARALLEL ROHRE Wall bracket OSLO 650/650-2 Made of galvanised steel Overhanging 500 mm Colour: DB 703 or all RAL- (classic- single shades), Hess-DB and Hess-Glimmer-colours. RAL pearl-mica-metallic-shades on request.


Light output 1




1 x LED			
Nominal lamp power	28 W	LOR	100%
Lamp flux	2757 lm	Total flux	2757 lm
Luminous efficacy	98 lm/W	Total power	28 W
CCT	3000 K		
CRI	80		



1 x LED			
Nominal lamp power	28 W	LOR	100%
Lamp flux	2451 lm	Total flux	2451 lm
Luminous efficacy	88 lm/W	Total power	28 W
CCT	3000 K		
CRI	80		



1 x LED			
Nominal lamp power	28 W	LOR	100%
Lamp flux	2609 lm	Total flux	2609 lm
Luminous efficacy	93 lm/W	Total power	28 W
CCT	3000 K		
CRI	80		


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

28 W
2623 lm
94 lm/W
3000 K
80

LOR
Total flux
Total power

100%
2623 lm
28 W


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

20 W
2072 lm
104 lm/W
3000 K
80

LOR
Total flux
Total power

100%
2072 lm
20 W


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

20 W
1843 lm
92 lm/W
3000 K
80

LOR
Total flux
Total power

100%
1843 lm
20 W


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

20 W
1963 lm
98 lm/W
3000 K
80

LOR
Total flux
Total power

100%
1963 lm
20 W


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

20 W
1973 lm
99 lm/W
3000 K
80


LOR
Total flux
Total power

100%
1973 lm
20 W




1 x LED

Nominal lamp power	15 W	LOR	100%
Lamp flux	1451 lm	Total flux	1451 lm
Luminous efficacy	97 lm/W	Total power	15 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	15 W	LOR	100%
Lamp flux	1291 lm	Total flux	1291 lm
Luminous efficacy	86 lm/W	Total power	15 W
CCT	3000 K		
CRI	80		



1 x LED

Nominal lamp power	15 W	LOR	100%
Lamp flux	1373 lm	Total flux	1373 lm
Luminous efficacy	92 lm/W	Total power	15 W
CCT	3000 K		
CRI	80		



1 x LED

Nominal lamp power	15 W	LOR	100%
Lamp flux	1381 lm	Total flux	1381 lm
Luminous efficacy	92 lm/W	Total power	15 W
CCT	3000 K		
CRI	80		

Mounting mode

Wall mounted

Shape and measurements

Length: 32.48 in

Width: 25.59 in

Height: 32.76 in

Adjustability

Fixed

Electric

System power: 15-28 W

Protection

IP: 65