# Product data sheet


LERS4B/LESQS4B LED 4" SHALLOW ROUND AND SQUARE CYLINDERS
LE_4B20D010 EC4B10208030 4LBS1GPH
COOPER LIGHTING



IP 47

Mounting: ceiling, wall, stem, aircraft cable; Down or up/down styles, Shallow extruded housing; Die-cast or spun aluminum reflectors, 6 color temperatures: 2400K, 2700K, 3000K, 3500K, 4000K and 5000K CCT, CRI: 80, 90 or 97; D2W™ option from 3000K to 1850K, Lumens: 1,000-3000; W2N Tunable White 2700K-6500K or 2000K-5000K, Colors: Matte Black, White, Bronze and Silver paint finishes, Standard 0-10V dimming down to 1%, ENERGY STAR® qualified, 5-year warranty, Integral or remote driver options

## Light output 1 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 3000 K |
| Nominal lamp power | 20.8 W | CRI | 100 |
| Total flux | 2117 lm | LOR | 100% |
| Luminous efficacy | 102 lm/W | Total power | 20.8 W |

### Mounting mode

Ceiling recessed

### Shape and measurements

Length: 3.94 in
Width: 3.94 in
Height: 3.94 in

### Adjustability

Fixed

### Electric

System power: 20.8 W

### Protection

IP: 47