



Product data sheet

NEPTUN INDUSTRY LED 15000 PC-T OPTICS-AREA EDD IP66 21 840 / 1563X115X110MM ZASILANIE PRZELOTOWE 16A ...
19.4343.I723.21
LUXIONA



Indoor luminaire. Assembly: directly mounted to ceiling construction or surface mounted on slings. The body material is polycarbonate.
Colour - RAL 9006 (grey). Dimensions: 1563 x 115 x 110 mm. Diffuser: PC-T (transparent polycarbonate). The efficiency of the optical system is 88,84%. Beam angle: (C0-C180) / (C90-C270) - 115,2° / 114°. Light source type: LED. Colour of the light 4000 K. SDCM=3. CRI>80. Lifetime of LED sources: 90000 h L80/B10. Luminaire luminous flux: 13162,3 lm. Power of luminaire: 84,7 W. Luminaire's light efficiency: 155,4 lm/W. Driver: DIM DALI (EDD). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 13 (B10), 21 (B16), 22 (C10), 32 (C16). Operating temperature range: -25 ÷ 35° C. Protection degree: IP66. Impact resistant: IK10. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0.

Light output 1



5 x LED			
Nominal lamp power	16.94 W	LOR	52%
Lamp flux	2963 lm	Total flux	7768 lm
Luminous efficacy	175 lm/W	Total power	84.7 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 61.54 in

Width: 4.53 in

Height: 4.33 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 84.7 W

Controller: DALI

Appliance Class: I

Protection

IP: 66

IK: 10

Other operating numbers

Ambient temperature range: -13...95°F