

# Product data sheet

EVOLUME 1 730 CLO CROSSING  
304190  
FAGERHULT




IP  
66

IK  
08

Installation Post top luminaire as standard can be mounted on a Ø 48-60 mm post top or post arm. Accessories for 76 mm and twin mounting are ordered separately, please see Accessories. Tilting function  $\pm 15^\circ$ . Post height 3–8 m. Connection Connection cable 10 m 3x1.5 mm<sup>2</sup> type H07RN-F. DALI version available on request, delivered with a 5-pin cable. Other cable versions on request. Design Body and post bracket in cast aluminium. Aluminium-zinc coated screws. Ballast is built into the luminaire. Flanges for optimum cooling. Screen printed safety glass. Optics The lenses are specially developed for crossings (right-hand traffic). Dimming CLO (Constant Light Output) maintains the correct light from the luminaire for the duration of its service life. DALI version is available on request. Standard Colour Alu-grey (RAL 9006, semi-gloss).

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	104 W	CRI	70
Total flux	12376 lm	LOR	100%
Luminous efficacy	119 lm/W	Total power	104 W

## Mounting mode

Pole top mounted

## Shape and measurements

Length: 21.85 in  
Width: 13.70 in  
Height: 4.68 in

## Adjustability

Tiltable

## Design

Color of housing: Silver gray

## Electric

System power: 104 W

## Protection

IP: 66  
IK: 08