


Product data sheet

BLIZ ROUND 30 S/EW 30W 830 AN-96 DALI
304225
PERFORMANCE IN LIGHTING



Part number: 304225. Serie: BLIZ. Wall and ceiling mounted LED luminaire for indoor and outdoor, comprising: Die-cast aluminium housing and trim, polyester powder coat finish ISO 9227/12944. ISO 9223 (C5) . Pressed glass diffuser, internally coated. Anti-ageing custom moulded silicone sealing gasket(s). Through-wiring designed. Built-in driver. Stainless steel locking hardware. Product data | ETIM Group: EG000027. ETIM Class: EC002892. General information | Lampholder: LED. Lightsource lumen output [lm]: 4236. Luminaire lumen output [lm]: 2178. Luminaire wattage [W]: 30 W. Luminous efficacy [lm/W]: 73. CRI: 80. Colour temperature [K]: 3000. Colour / Finishing: AN-96 / Anthracite gray / Textured. IP degree of protection: IP65. IK08 5J xx5. Protection class: I. Optic: S/EW - Symmetric Extra-Wide. Net weight [kg]: 3.636. Overall diameter [mm]: 302. Overall width [mm]: 84. Mechanical features | Shape: Round 300 mm. Housing material: Aluminium. Diffuser material: Glass. Electrical features | Voltage type: AC/DC. Input voltage [V AC]: 220/240. Input frequency [Hz]: 0/50/60. Power factor / COS Φ : 0.9. Input voltage [V DC]: 176/276. Inrush current [A/ μ s]: 5 / 50. C10 1.5 mm²: 52. C16 2.5 mm²: 85. B10 1.5 mm²: 31. B16 2.5 mm²: 50. Dimmable DALI. Installation | Application area: PROFESSIONAL OUTDOOR. Mounting type: Bulkheads. Min. ambient temperature [°C]: -20. Max. ambient temperature [°C]: 30. Through wiring connection. Light features | Lamps: 1. ILCOS: DSR. MacAdam: 3. Lumen maintenance: L80B10@60000h. Distribution of light emission: Direct. Certifications | CE certified. EAC certified. UKCA certified. RCM certified. Mountable on normally inflammable surfaces.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	30 W	CRI	80
Total flux	2178 lm	LOR	46%
Luminous efficacy	73 lm/W	ULOR	5%
		Total power	30 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 11.89 in

Width: 11.89 in

Height: 3.31 in

Adjustability

Fixed

Electric

System power: 30 W

Appliance Class: 0

Protection

IP: 65

IK: 08

Designation labels: CE, F