



Product data sheet

LIGHT LINEAR PT 9 STREET & AREA LIGHTING LUMINAIRES
LI-21251-T4-8040
LIGMAN




- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 2700K,3000K and 4000K - Die-cast aluminium housing - Extruded aluminium column - Pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 304 with zinc flake coating (ZFC) - Durable silicone rubber gasket - Clear toughened glass - High-efficiency polycarbonate lens - Integral control gear - Maximum wind load resistance is 100 km/h - Surge protection 10kV

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	30.1 W	CRI	80
Total flux	3595 lm	LOR	100%
Luminous efficacy	119 lm/W	Total power	30.1 W

Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	30.1 W	CRI	80
Total flux	3595 lm	LOR	100%
Luminous efficacy	119 lm/W	Total power	30.1 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 22.20 in

Width: 7.87 in

Height: 3.54 in

Weight: 26.5 kg

Adjustability

Fixed

Electric

System power: 60.2 W

Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

Protection

IP: 65

IK: 08

Surface temperature: 40°C