


Product data sheet

LUXCAN ZOOM 2000 20-60° E 34 930 3F
19.4370.1131.34
LUXIONA



Indoor luminaire. Assembly: mounted on a three-phase track. The body material is aluminum. Colour - RAL 9016 (white). Luminaire dimensions: Ø80 x 185 mm. Diffuser: optical system based on PMMA lenses. Beam angle: 20°-60°. Light source type: LED. Colour of the light 3000 K. SDCM=3. CRI>90. Lifetime of LED sources: 100000 h L80/B10. Luminaire luminous flux: 1578/1682/1734 (20/40/60°) lm. Power of luminaire: 12,8 W. Luminaire's light efficiency: 123,3/131,3/135,4 (20/40/60°) lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 30 (B10), 50 (B16), 50 (C10), 80 (C16). Operating temperature range: 5 ÷ 35° C. Protection degree: IP20. Impact resistant: IK04. Protection against electric shock: II. Photobiological risk class (IEC/EN 62471): RG0.

Light output 1



1 x LED			
Nominal lamp power	12.8 W	LOR	83%
Lamp flux	1880 lm	Total flux	1569 lm
Luminous efficacy	147 lm/W	Total power	12.8 W
CCT	3000 K		
CRI	90		

Mounting mode

Ceiling mounted

Shape and measurements

Height: 7.28 in
Diameter: 3.15 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 12.8 W
Appliance Class: II

Protection

IP: 20
IK: 04

Other operating numbers

Ambient temperature range: 41...95°F