

Product data sheet

HOSPITALITY LIGHTING
V1-R0-00504-20D01-2019030 COSMO 1200 MM SURFACE MOUNTED 190W 3000K DALI
VARTON




IP
40

IK
03

• Round luminaire with homogenous illumination • Material: Stainless steel housing Application • Offices • Corridors • Lobbies • Reception areas • Hospitality (restaurants, hotels, coffee bars) Installation • Surface-mounted Input voltage (AC, 50Hz), V: 220...240 AC frequency, Hz: 50 Flicker, %: 5 Climatic modification and category of placement: YX/J4 Protection class: II Housing material: Aluminium Mounting method: Surface mounting Ingress protection (IP): IP40 Impact resistance: IK03 Power factor: 0,95 https://www.varton.ru/products/intererno-osveshchenie-dekorativnoe-osveshchenie/cosmo/cosmo-1200-mm-nakladnye/svetodiodnyy-svetilnik-var-ton-cosmo-nakladnoy-190-vt-1200kh115-mm-3000-k-s-rasseivatelem-opal-ral900_1/

Light output 1



1 x LED			
Nominal lamp power	190 W	LOR	100%
Lamp flux	16000 lm	Total flux	15999 lm
Luminous efficacy	84 lm/W	Total power	190 W
CCT	3000 K		
CRI	90		

Mounting mode

Ceiling mounted

Shape and measurements

Height: 4.53 in
Diameter: 47.24 in

Adjustability

Fixed

Electric

System power: 190 W

Protection

IP: 40
IK: 03