


Product data sheet

COCO M 48V SPOT DIM DALI 4000K NTW
A5530212NTW
ARKOSLIGHT



A lightweight and powerful solution. Coco is a spotlight with a qualitative and uniform light distribution and provides great freedom of light emissions with four opening angles -flood, medium, spot and superspot - a 360° rotation and a 90° tilt. With an exceptional lm/W ratio, it can be fitted with various accessories: anti-glare honeycomb and anti-glare screen, which reduce glare to facilitate visual comfort, and the linear filter, which sets a linear light distribution. Coco invites one to interact with the light through a version with integrated dimmer, enabling one to adjust the desired intensity in each luminaire. Its tunable white version replicates the effects of natural light by regulating the intensity and colour temperature.

Light output 1



1 x LED			
Nominal lamp power	11.6 W	LOR	87%
Lamp flux	2200 lm	Total flux	1914 lm
Luminous efficacy	190 lm/W	Total power	11.6 W
CCT	4000 K		
CRI	90		

Mounting mode

Ceiling mounted, Contact rail

Shape and measurements

Length: 4.65 in
Width: 6.54 in
Height: 4.33 in

Adjustability

Rotatable, Tilttable

Design

Designer: Rubén Saldaña

Electric

System power: 11.6 W

Protection

IP: 20