Product data sheet


ASTRA S LED PRO 3600LM 830 AR5 IP66 I CL. WIRE 0,7M PLUG/GN 25W
436260
LENA LIGHTING



IP 66 IK 08

436260 ASTRA S LED PRO 3600lm 830 AR5 IP66 I cl. WIRE 0,7M PLUG/GN 25W LED road luminaire with high luminous efficiency and energy-saving integrated LED module. Self-cleaning body made of polypropylene (PP) with fibreglass (FG), handle made of aluminium. The luminaire uses directional lens matrices (made of polycarbonate PC). The luminaire is characterised by a high IP66 ingress protection rating and mechanical impact resistance. The integrated bracket, which is adjustable in increments of 5 degrees, allows adjustment from: -5° to +15° (top, on pole); -5° to +15° (side, on boom). Supplied with 0.7m of H07RN-F cable as standard.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	25 W	CRI	80
Total flux	3600 lm	LOR	100%
Luminous efficacy	144 lm/W	Total power	25 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 16.34 in
Width: 6.93 in
Height: 2.95 in

Adjustability

Rotatable, Tiltable

Electric

System power: 25 W
Appliance Class: I

Protection

IP: 66
IK: 08
Designation labels: CE

Other operating numbers

Ambient temperature range: -13...113°F