


# Product data sheet

METRO GRAPHITE 180LM 2700K RA>80 TRAILING EDGE DIMMING  
7021986236910  
SG ARMATUREN



Stylishly clean wall luminaire giving attractive up and down light or just down light. Replaceable light source (included). Made of powder-coated die-cast aluminium with glass diffuser, Option of either visible or concealed connection, and connectors between wall fittings and luminaire. Wall fittings with clips for additional wiring. Light distribution Direct Light technic LED (exchangeable) GU10 4.5W 2700K Ra>80 SDCM 4 L70/B50 >40,000 hrs Ta=25°C Control/Dimming Trailing edge dimming Protection Class II IP65 IK07 Energy and approvals A CE Materials and finish Housing: Aluminium Colour: Graphite Optics: Tempered glass Mounting/Connection Surface, Indoor / Outdoor Screwless terminal block

## Light output 1



1 x LED			
Nominal lamp power	4.5 W	LOR	100%
Lamp flux	180 lm	Total flux	180 lm
Luminous efficacy	40 lm/W	Total power	4.5 W
CCT	2700 K		
CRI	80		

## Mounting mode

Wall mounted

## Shape and measurements

Length: 3.54 in  
Width: 5.79 in  
Height: 4.72 in

## Adjustability

Fixed

## Electric

System power: 4.5 W  
Appliance Class: II

## Protection

IP: 65  
IK: 07