Product data sheet

RECESSED DIRECTIONAL SPOTLIGHT NOVO 2 SQUARE INNER RING SET BACK SQUARE 8.9W 950LM CRI > 90 2700K 47M. 2010.9607 - NOVO2 SS SB CR68 LED950-927-L35 WH ONF

REGENT



IP 44 IK 07

Recessed directional spotlight Novo 2 Square inner ring set back, with LED, system power: 8.9 W, luminous flux of luminaire 950 lm, colour rendering index CRI > 90, colour temperature 2700 K, warm white, colour tolerances SDCM 3, lifetime LED L90 50'000 h, photobiological safety: the luminaire poses no danger (RG0), 230 V, rated current: 47 mA, direct light emission, housing in die-cast aluminium, with ceiling trim, white, RAL 9016, with lens, 35, 1 integral control gear, ON/OFF, high-quality die-cast aluminium housing, reduced installation time thanks to fully pre-assembled luminaire, including connection to control gear, with through-wiring option, suitable for ceiling thicknesses from 1 to 45 mm protection class II, ingress protection IP20 / IP44, glow wire test 850 °C, impact strength: IK 07 this product contains a light source of energy efficiency class D and EPREL registration number: 2018970 L = 78 mm, B = 78 mm, ceiling cutout □ 68 mm up to 73 mm, ET = 95 mm, swivelling 15°

Light output 1



1 x LED

Nominal lamp power	9.2 W	LOR	100%
Lamp flux	950 lm	Total flux	950 lm
Luminous efficacy	103 lm/W	Total power	8.9 W
CCT	2700 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 0.04 in
Width: 0.04 in
Height: 0.04 in
Weight: 0.749 kg

Adjustability

Rotatable, Tiltable

Design

Color of housing: White

Electric

System power: 8.9 W
Appliance Class: II

Protection

IP: 44
IK: 07