


# Product data sheet

PRODISC III WIT  
40009370  
PROLUMIA




Light source: SMD 2835 LED Beam angle: 120° Color temperature switchable: 3000K/4000K Light output switchable: 1700Lm/1190Lm/850Lm Operating temperature: -25°C - +50°C (Sensor versie Sensor version: -25°C – +40°C, emergency mode version: 0°C – +50°C, emergency mode + sensor version: 0°C – +40°C) Rated life hours: > 100,000 LED driver (included): CE Input: 220-240V AC 50/60Hz Electrical safety class: Class II Power factor: > 0.90 Autonomy: 1 hour

## Light output 1




### 1 x LED

|                    |          |             |         |
|--------------------|----------|-------------|---------|
| Nominal lamp power | 10 W     | LOR         | 100%    |
| Lamp flux          | 1130 lm  | Total flux  | 1130 lm |
| Luminous efficacy  | 113 lm/W | Total power | 10 W    |
| CCT                | 3000 K   |             |         |
| CRI                | 80       |             |         |




### 1 x LED

|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Nominal lamp power | 7 W      | LOR         | 100%   |
| Lamp flux          | 850 lm   | Total flux  | 850 lm |
| Luminous efficacy  | 121 lm/W | Total power | 7 W    |
| CCT                | 4000 K   |             |        |
| CRI                | 80       |             |        |




### 1 x LED


|                    |          |             |         |
|--------------------|----------|-------------|---------|
| Nominal lamp power | 15 W     | LOR         | 100%    |
| Lamp flux          | 1700 lm  | Total flux  | 1700 lm |
| Luminous efficacy  | 113 lm/W | Total power | 15 W    |
| CCT                | 4000 K   |             |         |
| CRI                | 80       |             |         |




|                    |          |             |         |
|--------------------|----------|-------------|---------|
| <b>1 x LED</b>     |          |             |         |
| Nominal lamp power | 10 W     | LOR         | 100%    |
| Lamp flux          | 1190 lm  | Total flux  | 1190 lm |
| Luminous efficacy  | 119 lm/W | Total power | 10 W    |
| CCT                | 4000 K   |             |         |
| CRI                | 80       |             |         |



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| <b>1 x LED</b>     |         |             |        |
| Nominal lamp power | 16 W    | LOR         | 100%   |
| Lamp flux          | 270 lm  | Total flux  | 270 lm |
| Luminous efficacy  | 17 lm/W | Total power | 16 W   |
| CCT                | 4000 K  |             |        |
| CRI                | 80      |             |        |



|                    |          |             |         |
|--------------------|----------|-------------|---------|
| <b>1 x LED</b>     |          |             |         |
| Nominal lamp power | 15 W     | LOR         | 100%    |
| Lamp flux          | 1610 lm  | Total flux  | 1610 lm |
| Luminous efficacy  | 107 lm/W | Total power | 15 W    |
| CCT                | 3000 K   |             |         |
| CRI                | 80       |             |         |



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| <b>1 x LED</b>     |          |             |        |
| Nominal lamp power | 7 W      | LOR         | 100%   |
| Lamp flux          | 807 lm   | Total flux  | 807 lm |
| Luminous efficacy  | 115 lm/W | Total power | 7 W    |
| CCT                | 3000 K   |             |        |
| CRI                | 80       |             |        |

**Mounting mode**

Ceiling mounted, Wall mounted

**Shape and measurements**

Height: 2.48 in

Diameter: 13.19 in

**Electric**

System power: 7-16 W

Appliance Class: I

**Protection**

IP: 44

IK: 10