Product data sheet


LIGHTALK 15 SURFACE FACADE LUMINAIRES
LA-30034-W-40
LIGMAN



IP 67 IK 08


- Lamp LED - Colour RGBW30, RGBW40, - Die-cast aluminium end-caps - Extruded aluminium housing and sheet aluminium front frame - Pre-treated before powder coating ensuring high corrosion resistance - Single cable entry, through wiring upon request - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear toughened glass - Integral control gear - DC24V input, DMX512 address with constant current control for RGBW products

Light output 1 (integrated)




Lamp type	LED	CCT	
Nominal lamp power	8 W	CRI	
Total flux	116 lm	LOR	100%
Luminous efficacy	14 lm/W	ULOR	50%
		Total power	8 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	14 W	CRI	80
Total flux	1362 lm	LOR	100%
Luminous efficacy	97 lm/W	ULOR	50%
		Total power	14 W

Light output 3 (integrated)



Lamp type	LED	CCT	0 K
Nominal lamp power	8 W	CRI	-18
Total flux	452 lm	LOR	100%
Luminous efficacy	56 lm/W	ULOR	50%
		Total power	8 W

Light output 4 (integrated)



Lamp type	LED	CCT	
Nominal lamp power	6 W	CRI	
Total flux	208 lm	LOR	100%
Luminous efficacy	35 lm/W	ULOR	50%
		Total power	6 W

Mounting mode

Wall mounted, Floor mounted

Shape and measurements

Length: 1.46 in
Width: 24.02 in
Height: 3.54 in
Weight: 3.7 kg

Adjustability

Free

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 36 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 67
IK: 08
Surface temperature: 40°C