

Product data sheet

MEGA CONE
621106.0031.19
RZB




IP
65

IK
04

Series: MEGA CONE Attractive wall luminaire with innovative housing design and high-quality LED optics. Housing made of corrosion-resistant die-cast aluminium, seawater-resistant powder-coated (C4, in accordance with ISO 12944-6). C5 coating available on request. With membrane valve as a standard to avoid condensed water. Luminaire head made of corrosion-resistant pressure die-cast aluminium, powder-coated, with clear glass cylinder and conical reflector. Fixing on the wall outside the sealed volume, drill hole deviations can be compensated. Screwless luminaire fixing via RZB Gravolock System. Connection box on base, max. 2 x 3 x 2.5 mm² for through wiring. With integrated HF movement sensor and light sensor. Functional parameters of the motion detector (wall mounting up to 2.5 m): HF detector 5.8 GHz with integrated corridor function. Detection angle 30°-150°. Radial detection range up to 6 m, depending on installation height. Hold time, daylight threshold and sensitivity adjustable via app. Sensors can be networked via Bluetooth. Colour: anthracite metallic (DB703) Length: 160 mm Width: 115 mm Height: 249 mm Lamp: LED System power: 10 W Rated luminous flux: 600 lm Luminous efficiency: 60 lm/W Control gear: Sensor converter Protection class: I Type of protection: IP 65

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	10 W	CRI	80
Total flux	600 lm	LOR	100%
Luminous efficacy	60 lm/W	ULOR	50%
		Total power	10 W

Mounting mode

Wall mounted

Shape and measurements

Length: 4.53 in
Width: 6.30 in
Height: 9.80 in

Adjustability

Fixed

Electric

System power: 10 W

Protection

IP: 65
IK: 04