



# Product data sheet

KAPPA LED  
514091  
FLOS



• Bollard for outdoor installation on floor. • Configuration: Extruded aluminium body, aluminium base with 15 micron anodizing for high resistance to corrosion. Methacrylate diffuser. Double layer coating for high resistance to corrosion: The aluminium components are painted with a double coat using powders which are complaint with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents).The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting.

## Light output 1 (integrated)



Lamp type	LED	CCT	6000 K
Nominal lamp power	2.3 W	CRI	70
Total flux	68 lm	LOR	100%
Luminous efficacy	30 lm/W	ULOR	78%
		Total power	2.3 W

## Mounting mode

Standing / Bollard

## Shape and measurements

Height: 35.43 in

Diameter: 1.89 in

## Adjustability

Fixed

## Electric

System power: 2.3 W

Appliance Class: III

## Protection

IP: 65

IK: 06