



Product data sheet

MERCMASTER LED 4000 LUMENS 4000K CCT DIFFUSED POLYCARBONATE GLOBE NEMA TYPE V I/MLLED3ND5
 APPLETON (EMERSON EGS)



Mercmaster LED Low Profile Series Pendant/Ceiling/Wall/Stanchion Mount 3/4" NPT Hub Diffused Polycarbonate Globe NEMA Type V Symmetrical 4000 K CCT/80 CRI Voltage- BU-120-277V, 50/60Hz, 125-300 Vdc BH-347-480 Vac, 50/60Hz B2-24-48 Vdc Class I, Division 2, Groups A, B, C, D Class I, Zone 2, AEx ec IIC Zone 21, AEx tb IIIC Class I, Zone 2, Ex ec IIC Class II, Division 1, Group E, F, G Zone 20, Group IIIC Class II, Division 2, Group F, G Class III Simultaneous Exposure Type 3R, 4, 4X IP66/IP67 IK08 Suitable for Use in Wet Locations Marine Outside Type (Salt Water) DLC Qualified Product listed Refer to catalog for additional options

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	38 W	CRI	80
Total flux	4164 lm	LOR	100%
Luminous efficacy	110 lm/W	Total power	38 W

Mounting mode

Pendant, Pole top mounted, Ceiling recessed

Shape and measurements

Height: 6.57 in
 Diameter: 13.43 in

Adjustability

Fixed

Electric

System power: 38 W
 Appliance Class: I

Protection

IP: 66
 IK: 08
 Explosion zone suitability: 2, 20, 21