


# Product data sheet

REO OK 93050 S2  
202 372 811 933  
DELTA LIGHT




Luminaire, ceiling recessed (indoor use) from Deltalight, named REO OK 93050 S2, available in the colour(s): black, white. For recessed mounting, a round opening with a diameter of 98 mm is needed and a min. depth for recessing of 65 mm. This luminaire is equipped with LED array 5,8-8,6W / CRI>90 (R9: 52) / 3000K / 787-1089lm with an optional driver, suitable for currents of 350mA to 500mA. Light distributor: reflector 50°.

## Light output 1



1 x LED			
Nominal lamp power	9 W	LOR	73%
Lamp flux	1089 lm	Total flux	792 lm
Luminous efficacy	121 lm/W	Total power	12 W
CCT	3000 K		
CRI	90		



1 x LED			
Nominal lamp power	6 W	LOR	73%
Lamp flux	787 lm	Total flux	573 lm
Luminous efficacy	131 lm/W	Total power	8 W
CCT	3000 K		
CRI	90		

## Mounting mode

Ceiling recessed

## Shape and measurements

Height: 0.12 in  
Diameter: 3.23 in  
Weight: 0.3 kg

## Electric

System power: 8-12 W  
Appliance Class: II

## Protection

IP: 20  
Designation labels: CE