



Product data sheet

FIL45 SUR 840 1950 NW OP COMF DALI BK.
F41SF084MOPR840DB
LAMP



Suspended or mounted surface structure model FIL45 SUR 840 LAMP brand. Made in extruded recycled aluminum with a rate of 80%, with opal comfort diffuser made of a translucent polycarbonate diffuser and an optical film to achieve a controlled light distribution and low UGR<16. Model for LED MID-POWER, colour temperature 4000K with CRI80 and with electronic wiring Dali included. With IP43, except for suspended installation, which becomes IP20, IK07 protection rating. Insulation Class I. Photobiological safety group 0. LED life time: 70.000 L80 B10. Available finishes: White, black and grey. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Light output 1



1 x LED			
Nominal lamp power	16.5 W	LOR	100%
Lamp flux	1615 lm	Total flux	1613 lm
Luminous efficacy	98 lm/W	Total power	16.5 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 33.07 in
Width: 1.77 in
Height: 3.15 in

Adjustability

Fixed

Electric

System power: 16.5 W
Appliance Class: I

Protection

IP: 20
IK: 07