# Product data sheet


POWERVISION 4 SURFACE HIGH BAY LUMINAIRES
PW49-GP153-M-W40
LIGMAN



IP 66 IK 07

- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Extruded aluminium pre-treated before powder coating ensuring high corrosion resistance - Thermal heat dissipation body - Single cable entry - Through wiring on request - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear, impact-resistant, toughened glass diffuser - Integral control gear

## Light output 1 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 147 W | CRI | 80 |
| Total flux | 19489 lm | LOR | 100% |
| Luminous efficacy | 133 lm/W | ULOR | 100% |
| | | Total power | 147 W |

### Mounting mode

Ceiling mounted, Wall mounted

### Shape and measurements

Length: 32.20 in
Width: 11.22 in
Height: 11.81 in
Weight: 17.8 kg

### Adjustability

Fixed

### Design

Color of housing: Black, White, Silver gray

### Glare protection

Glare protection: UGR < 19

### Electric

System power: 147 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

### Protection

IP: 66
IK: 07
Surface temperature: 40°C