

Product data sheet


NADJA II (2-ARMED)
9.874.2072.05
LEIPZIGER LEUCHTEN



IP
55

Recommended mounting height 4.00 - 6.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack -Available in any RAL or DB colour without surcharge - Scope of supply includes painted special steel brackets - please order pole dia. 76 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet


Light output 1



1 x High pressure sodium vapour lamp

| | | | |
|--------------------|----------|-------------|----------|
| Nominal lamp power | 150 W | LOR | 77% |
| Lamp flux | 17000 lm | Total flux | 13118 lm |
| Luminous efficacy | 75 lm/W | Total power | 176 W |
| CCT | 2000 K | | |
| CRI | 25 | | |

Light output 2



1 x High pressure sodium vapour lamp

| | | | |
|--------------------|----------|-------------|----------|
| Nominal lamp power | 150 W | LOR | 77% |
| Lamp flux | 17000 lm | Total flux | 13118 lm |
| Luminous efficacy | 75 lm/W | Total power | 176 W |
| CCT | 2000 K | | |
| CRI | 25 | | |

Mounting mode

Pole top mounted

Electric

System power: 352 W

Shape and measurements

Height: 20.08 in

Diameter: 20.08 in

Protection

IP: 55