


# Product data sheet

MODSU 123 L68 E3  
MOD SURFACE/SUSPENDED UGR EMERGENCY  
DEXTRA




MOD Surface / Suspended UGR - 1200x300, IP40, IK08 Surface mounted luminaire, white powder coated steel body, high transmission microprism diffuser. Options: E3 - Emergency control gear (333 lumens output) ST3 - Emergency Selftest AT3 - Emergency Autotest S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function)\* H - High Frequency Dimming (Analogue 1-10v) RAS - Reacta Air Wireless occupancy and daylight dimming RLS - Reacta-Link Wireless Presence & Daylight Sensor RCS - Reacta-Control Wireless, Presence

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	39.9 W	CRI	80
Total flux	4441 lm	LOR	100%
Luminous efficacy	111 lm/W	ULOR	4%
		Total power	39.9 W

## Light output 2 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	3 W	CRI	80
Total flux	333 lm	LOR	100%
Luminous efficacy	111 lm/W	ULOR	4%
		Total power	3 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 23.62 in

Width: 23.62 in

Height: 4.02 in

## Adjustability

Fixed

## Electric

System power: 42.9 W

Ballast: ECG

## Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

## Protection

IP: 20

IK: 08

Designation labels: CE