


Product data sheet

DAMP-PROOF DIFFUSER LUMINAIRE SPLASH 34- 56W 4800- 8100LM C
2008.9149 - SPLASH 1572 LED4800-8100-840 WB PMMA ONF ML
REGENT



Damp-proof diffuser luminaire Splash for surface, wall, pendant mounting and mounting rail, with LED, system power: 34 - system power: 56 W, luminous flux of luminaire 4800 - luminous flux of luminaire 8100 lm, colour rendering index CRI > 80, colour temperature 4000 K, neutral white, colour tolerances SDCM 3, lifetime LED L90 71'000 h, L80 145'000 h, photobiological safety: the luminaire poses no danger (RG0), 230 V, nominal current: 4.2 A, direct light emission, wide beam, 1 integral control gear, ON/OFF, housing in acrylonitrile butadiene styrene (ABS), dark grey and diffuser in polymethyl methacrylate (PMMA), transparent, with chrome steel clamps, System power and choice of 6 luminous flux levels, can be set directly on the luminaire 34-38-42-45-52-56 W / 4800-5400-6000-6500-7400-8100 lm protection class I, ingress protection IP66, glow wire test 650 °C, impact strength: IK 06, for ambient temperatures -20 to +40 °C, this product contains a light source of energy efficiency class A and EPREL registration number: 1459375 L = 1572 mm, B = 95 mm, H = 100 mm

Light output 1



1 x LED

Nominal lamp power	49 W	LOR	100%
Lamp flux	8100 lm	ULOR	9%
Luminous efficacy	165 lm/W	Total flux	8100 lm
CCT	4000 K	Total power	56 W
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 61.89 in

Width: 3.74 in

Height: 4.37 in

Weight: 4.596 kg

Adjustability

Fixed

Design

Color of housing: Anthracite / graphite

Electric

System power: 56 W

Appliance Class: I

Protection

IP: 66

IK: 06