Product data sheet


RUBIN CLEAN ISO NO FRAME LED CRI95 10800 SLMR E IP65 940 KRG3K / 1200X600
19.4122.3641.34
LUXIONA



IP 65 IK 08

Indoor luminaire. Assembly: surface mounted on ceiling. The body material is steel sheet. Colour - white. Dimensions: 1174 x 574 x 69 mm. Diffuser: SLMR (laminated anti-reflective mat glass). The efficiency of the optical system is 80,12%. Beam angle: (C0-C180) / (C90-C270) - 100° / 100,2°. Light source type: LED. Colour of the light 4000 K. SDCM=3. CRI>95. Lifetime of LED sources: 60000 h L80/B10. Luminaire luminous flux: 9414 lm. Power of luminaire: 73,5 W. Luminaire's light efficiency: 128,1 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 9 (B10), 15 (B16), 15 (C10), 24 (C16). Operating temperature range: 5 ÷ 30° C. Protection degree: IP65. Impact resistant: IK08. Protection against electric shock: I. This is a medical device. Use it in accordance with the instructions for use.

Light output 1



6 x LED

Nominal lamp power	12.25 W	LOR	52%
Lamp flux	1958 lm	ULOR	26%
Luminous efficacy	160 lm/W	Total flux	6159 lm
CCT	4000 K	Total power	73.5 W
CRI	95		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 46.22 in
Width: 22.60 in
Height: 2.72 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 73.5 W
Appliance Class: I

Protection

IP: 65
IK: 08

Other operating numbers

Ambient temperature range: 41...86°F