
Product data sheet

KOMBIC 150 SF 2400 IP43 930 OP DA BR/WH
K21SF2040OP930DRW
LAMP



Suspended or ceiling mounting downlight model KOMBIC 150 SF by Lamp brand. Body made of white aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Shiny metalized interior reflector and optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CRI90. Luminaire with electronic wiring Dali included. Insolation Class I. Lifetime: >100.000 L90 B10.With IP43 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Light output 1



1 x LED

Nominal lamp power	19.5 W	LOR	100%
Lamp flux	1947 lm	Total flux	1945 lm
Luminous efficacy	100 lm/W	Total power	19.5 W
CCT	3000 K		
CRI	90		

Mounting mode

Ceiling mounted

Shape and measurements

Height: 7.09 in
Diameter: 5.91 in

Adjustability

Fixed

Electric

System power: 19.5 W
Appliance Class: I

Protection

IP: 40