
Product data sheet

LUCAS VIII (WALL FITTING BEADED) 9.828.2152.16



High-quality mirror optics provide good glare protection and enable mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet


Light output 1



1 x High pressure sodium vapour la	mp
------------------------------------	----

IP 55

Nominal lamp power	50 W	LOR	80%
Lamp flux	3500 lm	ULOR	4%
Luminous efficacy	45 lm/W	Total flux	2799 lm
CCT	2000 K	Total power	62 W
CRI	25		



1 x Hiah	pressure	sodium	vanour	lamn
I A LIIGH	pressure	Journan	vapour	ianip

	5 1			
Nom	ninal lamp power	70 W	LOR	80%
Lam	p flux	5600 lm	ULOR	4%
Lum	inous efficacy	54 lm/W	Total flux	4479 lm
CCT		2000 K	Total power	83 W
CRI		25		

Mounting mode
Wall mounted
Shape and measurements
Height: 22.44 in

Diameter: 22.44 in

Electric

System power: 62-83 W

Protection

IP: 55