


Product data sheet

OFFICE LIGHTING
V1-A0-00350-01OPS-4003550 A350 2.0 IP40 1195X295X50 MM 35W 5000K OPAL MICROWAVE SENSOR
VARTON



Versatile office luminaire. Stainless steel housing with white powder coating. Application: administrative facilities, lobbies. Recessed and surface-mounted. Compatible with the Armstrong Prelude 24 suspended ceiling systems. Input voltage (AC, 50Hz), V: 176...264 AC frequency, Hz: 50 Flicker, %: 2 Climatic modification and category of placement: YXJ14 Height/depth, mm: 50 Length, mm: 1195 Protection class: I Ingress protection (IP): IP40 Impact resistance: IK03 Width, mm: 295 Power factor: 0,95 https://www.varton.ru/products/ofisnoe-osveshchenie/a-seriya-2-0/a350-2-0-ip40-ofis-1195-295-analog-2-36/svetodiodnyy-svetilnik-varton-a350-2-0-ofisnyy-vstraivaemyy-nakladnoy-35-vt-5000-k-1195kh295kh50-mm-_6/

Light output 1



1 x LED			
Nominal lamp power	35 W	LOR	100%
Lamp flux	4480 lm	Total flux	4480 lm
Luminous efficacy	128 lm/W	Total power	35 W
CCT	5000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 47.05 in
Width: 11.61 in
Height: 1.97 in

Adjustability

Fixed

Design

Material impression: Matt
Color of housing: White

Glare protection

Glare protection: UGR < 19

Electric

System power: 35 W
Ballast: ECG

Protection

IP: 40
IK: 03
Designation labels: CE

Other operating numbers

Ambient temperature range: 68...95°F