



# Product data sheet

FLOODLIGHT PERFORMANCE ASYM 55X110 50 W 3000 K BK  
4058075353299  
LEDVANCE



Floodlight with wide beam, asymmetric light distribution for various application areas. Product features: High luminous efficacy: up to 140 lm/W. Asymmetric light distribution for various application areas. Angled (45°) mounting bracket and up to 180° tilting. Type of protection: IP66. Impact resistance: IK08. Ambient temperature in operation: -30...+50 °C. High surge protection: up to 10 kV (L/N-PE), 6 kV (L-N). Integrated breather for preventing condensation inside the luminaire. Connection via 2 m cable, wiring required. Product benefits: Energy savings of up to 90 % compared to halogen lamp floodlights. Energy savings of up to 45 % compared to luminaires that use conventional discharge lamps. Bright, robust and durable. Homogeneous luminance distribution and reduced glare. No upper light output ratio (ULOR 0%) when mounted at 0° tilt. Key hole to ensure ease of installation. 5 years guarantee. Areas of application: Direct replacement for luminaires using HID lamps. Outdoor use (IP66). Parking. Public areas. Industry. Sports facilities. Architectural lighting. D-sign according to EN 60598-2-24 for fire-risk commercial unit, e.g. by accumulation of dust.

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	50 W	CRI	80
Total flux	5800 lm	LOR	100%
Luminous efficacy	116 lm/W	Total power	50 W

## Mounting mode

Wall mounted

## Shape and measurements

Length: 12.36 in  
Width: 9.45 in  
Height: 2.48 in  
Weight: 2.6 kg

## Adjustability

Rotatable

## Design

Material impression: Aluminum  
Color of housing: Black

## Electric

System power: 50 W  
Appliance Class: I

## Protection

IP: 66  
IK: 08  
Designation labels: CE, ENEC

## Other operating numbers

Ambient temperature range: -22...122°F