Product data sheet


PAULA VI 9.646.3066.05 LEIPZIGER LEUCHTEN






Recommended mounting height 4.50 - 6.00 m, other heigts please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack -Available in any RAL or DB colour without surcharge - Scope of supply includes painted special steel brackets - please order pole dia. 76 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x High pressure mercury vapour lamp

5 1			
Nominal lamp power	125 W	LOR	83%
Lamp flux	6800 lm	Total flux	5651 lm
Luminous efficacy	41 lm/W	Total power	137 W
CCT	3400 K		
CRI	54		



1 x High pressure mercury va	pour lamp	
Nanainal Janan nauyar	00.14/	

Nominal lamp power	80 W	LOR	83%
Lamp flux	4000 lm	Total flux	3324 lm
Luminous efficacy	37 lm/W	Total power	89 W
CCT	3400 K		
CRI	54		

Mounting mode	Electric
Pole top mounted	System power: 89-137 W
Shape and measurements	Protection
Height: 28.74 in	IP: 55
Diameter: 28.74 in	