


Product data sheet

PURE 1 SPOT PRO TRACK
09.1071/HI PAR 51/20W/10°/25°/40°
FLOS




Luminaire for three-phase electric track installation. For very low voltage halogen lamps or standar and discharge lamps. Self-extinguishing ceramic or engineering plastic lamp holders, with single-pole, transparent electric wires with double teflon insulation.


Light output 1



1 x Metal halide lamp			
Nominal lamp power	20 W	Socket	Gx10
Lamp flux	1615 lm	LOR	49%
Luminous efficacy	81 lm/W	Total flux	789 lm
CCT	3000 K	Total power	20 W
CRI	80		



1 x Metal halide lamp			
Nominal lamp power	20 W	Socket	Gx10
Lamp flux	1615 lm	LOR	50%
Luminous efficacy	81 lm/W	Total flux	805 lm
CCT	3000 K	Total power	20 W
CRI	80		



1 x Metal halide lamp			
Nominal lamp power	20 W	Socket	Gx10
Lamp flux	1615 lm	LOR	54%
Luminous efficacy	81 lm/W	Total flux	870 lm
CCT	3000 K	Total power	20 W
CRI	80		

Mounting mode

Ceiling mounted

Electric

System power: 20 W
Appliance Class: I

Shape and measurements

Length: 1.69 in

Width: 4.34 in

Height: 5.31 in

Adjustability

Free

Protection

IP: 20