Product data sheet

CACTUS STRIP 200CM + 2 SPOT WOLF 48V 13W OTTICA/W 54° 84039106_200_8402704A/W

EXENIA









Pole mount system to use with WOLF LED projector for surface and wall mount installations. The CACTUS pole is available in three standard lengths of 600mm, 1000mm and 2000mm. Up to three WOLF LED projectors can be fitted on the CACTUS pole for 1000mm and 2000mm. Up to two LED projectors can be fitted on the 600mm CACTUS. Natural powder coat finish options include carbon grey, mud brown, matt sand, matt white textured and rust effect. A range of external drivers and accessories is available for this range to enable ON/OFF and DALI dimming.

Light output 1 (integrated)




| Lamp type | LED | CCT | 3000 K |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 8.7 W | CRI | 85 |
| Total flux | 213 lm | LOR | 100% |
| Luminous efficacy | 24 lm/W | Total power | 8.7 W |

Light output 2 (integrated)



| Lamp type | LED | CCT | 3000 K |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 12.8 W | CRI | 85 |
| Total flux | 1169 lm | LOR | 100% |
| Luminous efficacy | 91 lm/W | Total power | 12.8 W |

Light output 3 (integrated)



| Lamp type | LED | CCT | 3000 K |
|--------------------|---------|-----------|-----------|
| Nominal lamp power | 12.8 W | CRI | 85 |
| Total flux | 1169 lm | LOR | 100% |
| Luminous efficacy | 91 lm/W | Total pow | er 12.8 W |

Mounting mode

Standing / Bollard, Floor mounted

Shape and measurements

Length: 6.30 in Width: 6.30 in Height: 78.82 in

Adjustability

Free

Electric

System power: 34.3 W Appliance Class: III

Protection

IP: 65 IK: 08