
Product data sheet

LUCAS IX (WALL FITTING BEADED) 9.831.2056.16

LEIPZIGER LEUCHTEN








Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet


Light output 1



1 x High pressure sodium vapour lamp			
Nominal lamp power	100 W		
Lamp flux	10400 lm		
Luminous efficacy	72 lm/W		
CCT	2000 K		
CRI	25		

1 v High pressure codium vanour lamp

LOR	80%
ULOR	4%
Total flux	8319 lm
Total power	115 W



i x riigii pressure sodidiri vapodi lairip						
Nominal lamp power	70 W	LOR	80%			
Lamp flux	5600 lm	ULOR	4%			
Luminous efficacy	54 lm/W	Total flux	4479 lm			
CCT	2000 K	Total power	83 W			
CBI	25					

Mounting mode

Wall mounted

Shape and measurements

Height: 22.44 in Diameter: 22.44 in Electric

System power: 83-115 W

Protection

IP: 55