


# Product data sheet


SINUS CURVED SEGMENT DI/ID WHITE SAT. 45° R1440  
P33-H54-9016E2930L3S  
PLANLICHT



IP  
40


low output LED 3000K CRI 90 29,5W 3400lm DALI <https://katalog.planlicht.com/en-gb/search?q=sinus%20segment>

## Light output 1 (integrated)




|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 3000 K |
| Nominal lamp power | 7.38 W   | CRI         | 90     |
| Total flux         | 850 lm   | LOR         | 100%   |
| Luminous efficacy  | 115 lm/W | Total power | 7.38 W |

## Light output 2 (integrated)




|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 3000 K |
| Nominal lamp power | 7.38 W   | CRI         | 90     |
| Total flux         | 850 lm   | LOR         | 100%   |
| Luminous efficacy  | 115 lm/W | Total power | 7.38 W |

## Light output 3 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 3000 K |
| Nominal lamp power | 7.38 W   | CRI         | 90     |
| Total flux         | 850 lm   | LOR         | 100%   |
| Luminous efficacy  | 115 lm/W | Total power | 7.38 W |

Light output 4 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 3000 K |
| Nominal lamp power | 7.38 W   | CRI         | 90     |
| Total flux         | 850 lm   | LOR         | 100%   |
| Luminous efficacy  | 115 lm/W | Total power | 7.38 W |

Mounting mode

Pendant, Contact rail

Shape and measurements

Length: 41.06 in

Width: 18.98 in

Height: 3.94 in

Adjustability

Fixed

Electric

System power: 29.5 W

Protection

IP: 40