Product data sheet

ECLPANELTWCJR4X1
ECLPANELTWCJR4X1_2800K_FILTER LD
PROLIGHTS



IP 20 IK 08

The EclPanel TWCJR4x1 is a compact LED linear soft light that provides a beautiful, wide source of soft and precise colours. In addition to this, the EclPanel TWCJR4x1 comes with a full range of white presets, from daylight to tungsten tones, and produces a tremendous output whilst keeping high CRI, TLCI and TM-30 values. The EclPanel TWCJR4x1 has 3 precision rotatory knobs, with multiple stand-alone control modes: CCT with +/- green shift, CCT presets, HSI for total control of hue, saturation and intensity, RAW RGBW mode, XY and FX mode, allowing to scroll through the built-in cinema effects engine. The 2 sections are controlled individually or simultaneously, allowing to play on-board customizable, cinematic effects through its built-in engine or from a console. The EclPanel TWCJR4x1 has several colour control modes: RGBW, RGB, CMY, HSI, XY, RAW Direct, CCT Linear and CCT Presets with +/- green shift, source emulation and industry-standard colour gels. Despite its lightweight, it has an on-board driver, a built-in power supply, Wireless DMX (CRMX+W-DMX), network connectivity (Art-Net, sACN, Kling-Net) and low voltage inputs (24-36V and 48VDC) Features: 230W RGB + Warm White LED source CRI >94; R9 >95; TLCI >92 2 section pixel control and built-in lighting effects for cinema applications, colour gel matching Silent operation with multiple fan modes Wireless DMX (CRMX+W-DMX), Ethernet connectivity, low voltage inputs (24-36V, 48Vdc)

Light output 1



1 x LED

Nominal lamp power	219.8 W	LOR	100%
Lamp flux	16448 lm	Total flux	16481 lm
Luminous efficacy	75 lm/W	Total power	240 W
CCT	2855 K		
CRI	93		

Mounting mode

Pendant

Shape and measurements

Length: 30.00 in
Width: 2.51 in
Height: 7.98 in

Adjustability

Rotatable, Free

Electric

System power: 240 W
Controller: DMX
Color adjustable
Appliance Class: I

Protection

IP: 20
IK: 08
Surface temperature: 70°C
Designation labels: CE