## Product data sheet

DEFINE LED WALL MOUNT LUMINAIRE S122RDW-S865D935-4F0-1E-UDD-F

**COOPER LIGHTING** 








Wall Mount Slot family in 2", 3", 4" and 5" housing sizes, Specifiable to the nearest 1', Multiple lensing options: flush satin, drop, regressed and asymmetric, Multiple lumen packages, 0-10V dimming standard; DALI dimming available, 2700K, 3000K, 3500K, 4000K & 5000K correlated color temperatures, VividTune CCT tuning options from 3000K–5000K or 2700K-6500K, Integral Wavelinx and Stand-alone sensors available, Customizable in-wall, in-ceiling and wall-to-ceiling corners available, DLC listed configurations available

## Light output 1 (integrated)



| Lamp type          | LED     | CCT         | 3500 K |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 34.8 W  | CRI         | 90     |
| Total flux         | 2495 lm | LOR         | 100%   |
| Luminous efficacy  | 72 lm/W | Total power | 34.8 W |

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 48.00 in Width: 2.00 in Height: 0.39 in

Adjustability

Fixed

Electric

System power: 34.8 W

Protection

IP: 47