Product data sheet

FACET II 1200 WHITE 4700LM 4000K RA>80 DALI 5703821172004

SG ARMATUREN








Facet II is a slim, minimalistic luminaire with white powdercoating. With the direct/indirect light and glare-free optics in PMMA it is perfect for classrooms or open offices where light comfort is very important. The wall bracket (accessory) makes it a prefect choice for blackboard lighting. Plug-and-play solution for quick installation. Light distribution Direct/Indirect Light technic LED 29W 4000K Ra> 80 SDCM 3 L80/B10 >100,000 hrs L94 >50,000 hrs Control/Dimming DALI Protection Class I IP20 Materials and finish Housing: Sheet steel Colour: White (RAL 9010, 20% gloss) Optics: Acrylic (PMMA) Mounting/Connection Suspended, Indoor 2x2m wire kit w/loop M4 Cable 5x0,75mm² 2,5m white Max. luminaires per circuit breaker: B10: 13, B16: 24, C10: 21, C16: 38

Light output 1



1 x LED
Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

29 W
4700 lm
162 lm/W
4000 K
80

LOR	100%
ULOR	21%
Total flux	4701 lm
Total power	29 W

Mounting mode

Pendant

Shape and measurements

Length: 47.07 in Width: 4.41 in Height: 3.74 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 29 W Appliance Class: I

Protection

IP: 20