


# Product data sheet

SPIKE WHITE 880LM 3000K RA>80 TRAILING EDGE DIMMING  
7021986119107  
SG ARMATUREN



Very attractive wall luminaire for outdoor mounting. Comes only as a downlight with good light scattering via the efficient LED module, and a version that also has a small slit as an uplight, which makes high walls look nice. Both variants available with or without two 230 V power points concealed behind two tip-up lids with automatic closure. If you choose the version with connectors, there is a separate terminal strip for the connections. Easy mounting and option of control via integrated dimming relay makes Spike the modern choice for wall lighting. Made of powder-coated aluminium with a 10-year corrosion warranty. Light distribution Direct Light technic LED 10W 3000K Ra>80 SDCM 3 L70/B50 >50,000 hrs Control/Dimming Trailing edge dimming Protection Class I IP44 IK08 Materials and finish Housing: Aluminium Colour: White (RAL 9003) Optics: UV-stabilized polycarbonate Mounting/Connection Surface, Outdoor Screwless terminal block

## Light output 1



1 x LED			
Nominal lamp power	10 W	LOR	100%
Lamp flux	880 lm	Total flux	880 lm
Luminous efficacy	88 lm/W	Total power	10 W
CCT	3000 K		
CRI	80		

## Mounting mode

Wall mounted

## Shape and measurements

Length: 6.53 in  
Width: 6.01 in  
Height: 6.69 in

## Adjustability

Fixed

## Design

Color of housing: White

## Electric

System power: 10 W  
Appliance Class: I

## Protection

IP: 44  
IK: 08