
# Product data sheet

KOMBIC 150 SF 3700 IP43 840 OPAL WH/BK
K21SF3540OP840NWB
LAMP



Suspended or ceiling mounting downlight model KOMBIC 150 SF by Lamp brand. Body made of black aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. White interior reflector and optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CRI80. Luminaire with electronic wiring included. Insolation Class I. Lifetime: >100.000 L85 B10.With IP43 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

## Light output 1



1 x LED

| | | | |
|---|---|---|---|
| Nominal lamp power | 27.5 W | LOR | 100% |
| Lamp flux | 3091 lm | Total flux | 3088 lm |
| Luminous efficacy | 112 lm/W | Total power | 27.5 W |
| CCT | 4000 K | | |
| CRI | 80 | | |

### Mounting mode

Ceiling mounted

### Shape and measurements

Height: 7.09 in
Diameter: 5.91 in

### Adjustability

Fixed

### Electric

System power: 27.5 W
Appliance Class: I

### Protection

IP: 40