


# Product data sheet

LADOR 29 FLOODLIGHTS,PROJECTORS AND COLUMN  
LD-50171-W-8040  
LIGMAN



- Lamp LED - CCT / CRI 3000K CRI80, 4000K CRI80 - Die-cast aluminium housing - Pre-treated before powder coating ensuring high corrosion resistance - Thermal heat dissipation body - Adjustable: Tilt 80° (Up) & 40° (Down), Rotation 350° - Single cable entry - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency PMMA lens - Clear toughened glass - Integral control gear

## Light output 1 (integrated)



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Lamp type          | LED     | CCT         | 4000 K |
| Nominal lamp power | 10 W    | CRI         | 80     |
| Total flux         | 992 lm  | LOR         | 100%   |
| Luminous efficacy  | 99 lm/W | ULOR        | 100%   |
|                    |         | Total power | 10 W   |

## Mounting mode

Wall mounted

## Shape and measurements

Length: 2.48 in  
Width: 21.54 in  
Height: 4.33 in  
Weight: 1.6 kg

## Adjustability

Free

## Design

Color of housing: Black, White, Silver gray

## Glare protection

Glare protection: UGR < 19

## Electric

System power: 10 W  
Ballast: ECG  
Controller: Dimmable 1..10V, DALI  
Appliance Class: I

## Protection

IP: 65  
IK: 08  
Surface temperature: 40°C