



Product data sheet

6002/4128-0101-152-1111-55-8500
272233
STAHL



Linear luminaire With LED GRP Explosion-protected Type: 6002/4128-0101-152-1111-55 -8500 Spare of type: 6002/1182-5401-8145-0
Enclosure material: Polyester resin Translucent cover material: Polycarbonate Version: Standard Enclosure colour: Light grey (RAL 7035)
Number of lamps: 1 Lamp wattage: 18 W Light distribution: 120°x120° with diffusing glass Luminous flux: 2.890 lm Luminaire efficacy: 161
lm/W Colour temperature: 5.000 K LED Service life: L90B50 ≥ 100.000 h Dimensions (L x W x H): 700 x 184 x 125 mm AC rated operational
voltage: 110,00 - 240,00 V DC rated operational voltage: 110,00 - 250,00 V Application range (zones): 1 , 2 , 21 , 22 Gas explosion protection: II 2
G Ex db eb ib mb op is IIC T4 Gb Dust explosion protection: II 2 D Ex tb op is IIIC T100 °C Db Min. ambient temperature: -40 °C Max. ambient
temperature: +50 °C Note: Through wiring: Max. 3x16 A Max. ambient temperature 2: +60 °C Note: Through wiring 2: Max. 3x10 A Impact
strength (IK code): IK10 (IEC 62262) Diffuser: With diffuser Through wiring: With 5 conductors 2.5 mm² Ballast: 6045/211-120-10 Threaded
plate: 2x SS316L stainless steel Drilled holes: 4 x M25 Without Screw connections: Can be ordered as accessories Stopping plug: Can be
ordered as accessories Languages of the documentation: German English For further information, see: r-stahl.com WebCode 6002D

Light output 1



1 x LED			
Nominal lamp power	18 W	LOR	100%
Lamp flux	2890 lm	ULOR	2%
Luminous efficacy	161 lm/W	Total flux	2890 lm
CCT	5000 K	Total power	18 W
CRI	81		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 27.48 in
Width: 6.61 in
Height: 5.07 in

Adjustability

Fixed

Design

Material impression: Matt
Color of housing: Anthracite / graphite, Silver gray

Electric

System power: 18 W
Ballast: ECG
Integrated Switch: In housing
Appliance Class: I

Protection

IP: 66
IK: 10
Explosion zone suitability: 1

Other operating numbers

Ambient temperature range: -40...140°F