


Product data sheet

RT 44
451172.002.1
RZB



IP
44

IK
03

Series: RT44 Type of Protection: IP 44 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz "Base: aluminium, powder-coated; end caps: plastic; diffuser:" plastic, opal, with safety socket. Available Colours: pure white (RAL 9010) Type of Installation: Ceiling mounting, Wall (surface) Dimensions: L 677, B 55, H 87 Lamp: LED Life time: 50000 h (L70/B10) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 970lm System power: 10W Beam Angle: 180°/111° Unified Glare Ratio: 23,1 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	10 W	CRI	80
Total flux	970 lm	LOR	100%
Luminous efficacy	97 lm/W	ULOR	20%
		Total power	10 W

Mounting mode

Wall mounted

Shape and measurements

Length: 2.17 in
Width: 26.65 in
Height: 3.43 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 10 W

Protection

IP: 44
IK: 03