Product data sheet


MASTAUFSATZLEUCHTE SERA-2 ASY34 32LED 2700K
88.09900.0V00X
HESS



IP 66 IK 09


Auf-/Ansatzleuchte Sera-2 Leuchten Gehäuse aus Aluminium-Druckguss Ausladung Mastachse bis Leuchtenspitze 650 mm Leuchten Abdeckung aus Einscheibensicherheitsglas (IK09), bedruckt Neigungswinkel Aufsatzmontage 0°/+15° in 5° Schritten Mit elektronischem Vorschaltgerät (220-240V/50-60Hz) Schutzart IP66

Light output 1




1 x LED

Nominal lamp power	29.4 W	LOR	100%
Lamp flux	3553 lm	Total flux	3553 lm
Luminous efficacy	121 lm/W	Total power	29.4 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	24.8 W	LOR	100%
Lamp flux	2980 lm	Total flux	2980 lm
Luminous efficacy	120 lm/W	Total power	24.8 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	20.2 W	LOR	100%
Lamp flux	2396 lm	Total flux	2396 lm
Luminous efficacy	119 lm/W	Total power	20.2 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	38.5 W	LOR	100%
Lamp flux	4698 lm	Total flux	4698 lm
Luminous efficacy	122 lm/W	Total power	38.5 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	43 W	LOR	100%
Lamp flux	5248 lm	Total flux	5248 lm
Luminous efficacy	122 lm/W	Total power	43 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	33.9 W	LOR	100%
Lamp flux	4131 lm	Total flux	4131 lm
Luminous efficacy	122 lm/W	Total power	33.9 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	65.9 W	LOR	100%
Lamp flux	7846 lm	Total flux	7846 lm
Luminous efficacy	119 lm/W	Total power	65.9 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	61.3 W	LOR	100%
Lamp flux	7343 lm	Total flux	7343 lm
Luminous efficacy	120 lm/W	Total power	61.3 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	56.7 W	LOR	100%
Lamp flux	6834 lm	Total flux	6834 lm
Luminous efficacy	121 lm/W	Total power	56.7 W
CCT	2700 K		
CRI	80		



1 x LED

Nominal lamp power	52.2 W	LOR	100%
Lamp flux	6313 lm	Total flux	6313 lm
Luminous efficacy	121 lm/W	Total power	52.2 W
CCT	2700 K		
CRI	80		



1 x LED

Nominal lamp power	47.6 W	LOR	100%
Lamp flux	5786 lm	Total flux	5786 lm
Luminous efficacy	122 lm/W	Total power	47.6 W
CCT	2700 K		
CRI	80		

Mounting mode

Pole top mounted, Pole integrated

Shape and measurements

Length: 4.82 in
Width: 5.71 in
Height: 7.31 in

Adjustability

Tiltable

Electric

System power: 20.2-65.9 W

Protection

IP: 66
IK: 09