Product data sheet


GOLAS MAXI
911453.004
RZB



IP 20 IK 03

Series: Golas Type of Protection: IP 20 Protection Class: II Voltage: 220 - 240 V / 50 - 60 Hz Housing: powder coated die cast aluminium. Horizontal rotation range: 356°, vertical swivel range: 65°. Installation without tools thanks to spring fastening system. Heat resistant plastic ring. Lens made of plastic (polycarbonate) included, can be changed without tools. Lamp (LED) included. Converter in separate converter housing. With connected connecting cable between luminaire and converter housing. Available Colours: silver Type of Installation: Recessed ceiling mounting Dimensions: D 178, H 3 Lamp: LED Life time: 50000 h (L90/B10) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 2350lm System power: 24W Beam Angle: 12° Number of fittings B10A: 21 Number of fittings B16A: 34 Number of fittings C10A: 35 Number of fittings C16A: 57 Inrush current: 18,6A Unified Glare Ratio: 8,3 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	27 W	CRI	80
Total flux	2400 lm	LOR	100%
Luminous efficacy	89 lm/W	Total power	27 W

Mounting mode

Wall mounted

Shape and measurements

Height: 0.12 in
Diameter: 7.01 in

Adjustability

Rotatable, Tiltable

Electric

System power: 27 W

Protection

IP: 20
IK: 03