
Product data sheet


INP320LED-1200-J4-2-35E-33-11PCI-GS-PC
31-326-12J401
ATM LIGHTING



IP 65 IK 10

Custodial light fitting with LED modules, designed to provide very high shock resistance (IK11+) and to be mounted between wall and ceiling of a cell or a corridor. Robust construction and special security screws prevent unauthorized access and eliminate ligature risk. The housing is made of powder coated galvanized steel and the diffuser is made of thick polycarbonate. | Weight: 16kg | Ambient temperature range: -30÷45°C

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	40.4 W	CRI	80
Total flux	5190 lm	LOR	100%
Luminous efficacy	128 lm/W	Total power	40.4 W

Mounting mode

Wall mounted, Ceiling mounted

Shape and measurements

Length: 53.94 in
Width: 6.69 in
Height: 6.69 in

Adjustability

Fixed

Design

Material impression: Gloss
Color of housing: White
Designer: Michał Ramczykowski

Electric

System power: 40.4 W
Ballast: ECG
Suitable for feed-through wiring
Appliance Class: I

Protection

IP: 65
IK: 10
Designation labels: CE

Other operating numbers

Ambient temperature range: -22...113°F