


Product data sheet

DKN QUADRAT
10444.002.1
RZB




IP
40

IK
02

Series: DKN-Quadrat, seidenglanz Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 50 Hz Base: metal, galvanised. Diffuser fastening: tilt springs (DKN system: push/tilt system). Diffuser: hand-blown opal glass, silk finish. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: L 360, B 360, H 110 Lamp: LED Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK02 (0,20 Joule) Luminaire flux LED: 550lm System power: 16W Beam Angle: 124° Unified Glare Ratio: 14,3 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	16 W	CRI	80
Total flux	550 lm	LOR	100%
Luminous efficacy	34 lm/W	ULOR	18%
		Total power	16 W

Mounting mode

Wall mounted

Shape and measurements

Length: 14.17 in
Width: 14.17 in
Height: 4.33 in

Adjustability

Fixed

Electric

System power: 16 W

Protection

IP: 40
IK: 02