

Product data sheet

INDUSTRIAL AND WAREHOUSE LIGHTING
V1-IA-70157-03DA0-6702850 IRON 2.0 0,9 M 28W 5000K TRANSPARENT EM 1H
VARTON




IP
67

IK
01

Industrial linear luminaire with aluminium housing and a wide range of power. Diffuser: transparent (acrylic), opal (polycarbonate) Installation: Suspended and surface-mounted. Suspended 3-6 m height (mounting brackets included in package). Surface-mounted (mounting brackets included in package). The luminaire has a wire for connecting to the mains. Wire length 0.5 meter Application: Administrative facilities. Industrial facilities. Warehouses. Areas with high moisture and dust environment, and high reliability requirements. Power factor: 0,95 Input voltage (AC, 50Hz), V: 198...264 AC frequency, Hz: 50 Input voltage (DC), V: 190...280 Flicker, %: 5 Climatic modification and category of placement: YXJ11 Protection class: I Ingress protection (IP): IP67 Impact resistance: IK01 <https://www.varton.ru/products/promyshlennoe-osveshchenie/iron-2-0/iron-2-0-0-9-m/svetodiodnyy-svetilnik-var-ton-ayron-2-0-28-vt-5000-k-906kh109kh66-mm-klass-zashchity-ip67-s-akrilovy/>

Light output 1



1 x LED			
Nominal lamp power	28 W	LOR	100%
Lamp flux	2800 lm	Total flux	2800 lm
Luminous efficacy	100 lm/W	Total power	28 W
CCT	5000 K		
CRI	80		

Mounting mode

Ceiling mounted

Electric

System power: 28 W

Shape and measurements

Length: 35.67 in

Width: 4.29 in

Height: 2.60 in

Protection

IP: 67

IK: 01

Adjustability

Fixed