


Product data sheet


ADLQ 235/2000-840 W + DQ235-SM-G-D-W
0321882 + 0204432
RIDI



IP
20

Surface-mounted downlighter ADLQ 235 Design: Square surface-mounted downlighter with edge length 235 mm for ceiling and pendant mounting, with RIDI LED module. Luminaire body in steel, powder coated white (similar to RAL9016). Stable housing frame in galvanised steel with integrated fixture for toolless mounting of accessories (decorative frames and trims, order separately). Protection rating IP 40. Function module in white polycarbonate for mounting the reflector with bayonet catch. Diffusor in transparent, internally satinised polycarbonate to protect the LEDs, clipped into the function module (opal diffusor available on request). Colour rendering in index Ra \geq 80, colour temperature 3000 Kelvin (830) Electronic converter for LED, 220-240 Volt, 0/50-60 Hz and internal connector block 5x2.5mm². Suitable for direct voltage operation and use in central battery systems. Mounting: Direct ceiling mounting or with accessories for wire pendant mounting. ADLQ 235/ ... W Edge length 235 mm. High-reflectance white reflector in steel, powder coated similar to RAL9016. DQ235-SM-G-D-W Dekorscheibe aus Floatglas mattiert mit Dekorrahmen weiß

Light output 1



1 x LED			
Nominal lamp power	16 W	LOR	87%
Lamp flux	2100 lm	Total flux	1824 lm
Luminous efficacy	114 lm/W	Total power	16 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 9.25 in
Width: 9.25 in
Height: 8.98 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 16 W

Protection

IP: 20