Product data sheet


TRAFFIK R LED 50W 7550LM 4000K IP66 O41 - FOR LOCAL ROADS GRAY I
130292.5L111.071
LUG



IP 66 IK 08

Professional streetlight luminaire for LED light sources. Mounting: on outriggers ø60/48mm, on pillar ø60/48mm Body: high pressure die-cast aluminum Lateral Surface Wind Exposed: 0.033 m² Power: 220-240V 50/60Hz Available on request: DIM 1..10V, LLOC, twilight sensor, 10kV surge protection, NTC Additional information: Tilt adjustment: -10° to 90° (every 5°) Other remarks: the pole and boom are not part of the luminaire; luminaire available in protection class I and II Warranty: 5 years Application: local roads, express roads, town roads, residential area roads, area lighting, avenues, promenade, parking areas Type of optics: O41 - for local roads

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	50 W	CRI	70
Total flux	7550 lm	LOR	100%
Luminous efficacy	151 lm/W	Total power	50 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 24.21 in
Width: 9.06 in
Height: 3.15 in

Adjustability

Tiltable

Design

Color of housing: Silver gray

Electric

System power: 50 W
Appliance Class: I

Protection

IP: 66
IK: 08