## Product data sheet


VOLKMAR I (WALL FITTING) 9.840.0087.08 LEIPZIGER LEUCHTEN





For medium light requirements, mounting heights from 3.00 - 4.00 m. - Excellent uniform illumination, optimal glare protection - Luminaire body made of aluminium/galvanized steel sheet - Impact-resistant opal polyethylene attachment, UV-stabilized - Steel tubing galvanized and painted - Adapter jack connection -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



$\times$	Æ	B	$\sim$
$\times$	Æ	R	$\leq$
Æ	A.	X	ТТ.
H			),

1 x High pressure sodium vapour lamp			
Nominal lamp power	100 W	LOR	73%
Lamp flux	10400 lm	ULOR	28%
Luminous efficacy	66 lm/W	Total flux	7562 lm
CCT	2000 K	Total power	115 W
CRI	25		

Total power

1 x High pressure sodium vapour lamp			
Nominal lamp power	70 W	LOR	
Lamp flux	5600 lm	ULOR	
Luminous efficacy	49 lm/W	Total flux	

2000 K

25

TA.	XH	F8	H
-7			
H	$\checkmark$	$\bigvee$	XT.
X	Æ	Ŧ	$\times$

CCT

CRI

E	lectri	С	

System power: 83-115 W

## Protection

IP: 55 Designation labels: CE, F

## Height: 16.14 in

Shape and measurements

Mounting mode Wall mounted

Diameter: 16.14 in

73% 28% 4072 lm

83 W